



Cryosat Operational Polar Monitoring Product Formats

Table of Contents

1Change Log	1
2Purpose	1
3Sea Ice Products	2
3.1Sea Ice Thickness Products	2
3.1.1Data Citation	2
3.1.2ASCII Thickness Format	
3.1.3NetCDF Format	5
3.1.4GeoTIFF Format	

1 Change Log

Version	Date	Description
1.0	15-Apr-2015	Initial version
1.1	17-Apr-2015	Added netCDF format
1.2	24-Apr-2015	Added GeoTIFF format for whole Arctic
1.3	03-Feb-2016	Explanation of negative sea ice values in products.
		Correction to the proj.4 specification of the WGS84 ellipsoid in the projection used in GeoTIFF files.
1.4	23-Aug-2016	Added a new ASCII thickness complete grid product. This is a larger sized product which includes every grid point (including grid points where no thickness is calculated).
1.5	11-Dec-2018	Added Monthly thickness data files, from Nov 2010
		onwards.

2 Purpose

This document details product formats provided by the CryoSat Operational Polar Monitoring portal at <u>http://www.cpom.ucl.ac.uk/csopr</u>

3 Sea Ice Products

3.1 Sea Ice Thickness Products

Sea Ice near real time thickness products are currently available in ASCII, netCDF and GeoTIFF formats in either a whole Arctic 5km resolution or as individual sectors at 1km resolution.

For 5km resolution data, a circular operator of radius 25km is applied when gridding the data and all points receive equal weight.

For the 5km grids, two products are available. Firstly a product where only grid points with sea ice thickness data are included in the file (ie it is a sparse grid). Secondly a larger sized complete product which includes every point in the grid and grid points with no thickness data are set to 0.0.

For the 1km grid all grid points north of 60N are present.

For 1km resolution data, a circular operator of radius 5km is applied when gridding the data and all points receive equal weight.

Note that negative thickness values are a consequence of negative freeboard measurements (the height of sea ice above water). Large negative freeboard values (values below -0.3 m) are likely to be caused by errors in the retracking applied to sea ice floe waveforms, and are removed from our processing. However, slightly negative freeboards will occur due to random noise in the returns from thin ice floes, caused by radar speckle. These are included to ensure that the average freeboard, and therefore thickness, is not biased high.

3.1.1 Data Citation

Users of this data should cite the following in any publication that uses data or images from this service:

Laxon S. W., K. A. Giles, A. L. Ridout, D. J. Wingham, R. Willatt, R. Cullen, R. Kwok, A. Schweiger, J. Zhang, C. Haas, S. Hendricks, R. Krishfield, N. Kurtz, S. Farrell and M. Davidson (2013), CryoSat-2 estimates of Arctic sea ice thickness and volume, Geophysical Research Letters, 40, doi:10.1002/grl.50193.

3.1.2 ASCII Thickness Format

All files are provided in compressed gzip format (.gz) to reduce size.



3.1.2.1 File Naming

Whole Arctic 5km resolution:

2, 14, 28-day NRT products:

thk_<*days*>.map.<*DD*₁*MM*₁*YY*₁>_<*DD*₂*MM*₂*YY*₂>.txt.gz (sparse grid) thk_<*days*>.map.complete.<*DD*₁*MM*₁*YY*₁>_<*DD*₂*MM*₂*YY*₂>.txt.gz (complete grid)

High Resolution (1km) Area sector files :

<days>day_x<*X*>y<*Y*>.map. .<*DD*₁*MM*₁*YY*₁>_<*DD*₂*MM*₂*YY*₂>.txt.gz

where *<days>* is either 02, 14 or 28 days, corresponding to the period covered.

 $<DD_1MM_1YY_1>$ is the date of the start of the period covered $<DD_2MM_2YY_2>$ is the date of the end of the period covered

<X> and <Y> are the sector identifiers. There are 36 sectors (as a 6x6 grid) arranged from the bottom left of the Arctic map and spaced every 1110km, such that X=1, Y=1 is the bottom left, and X=6, Y=6 is top right.

Monthly products:

thk_<year>_<month>.map.txt.gz (sparse grid)
thk_<year>_<month>.map.complete.txt.gz (complete grid)

Archive seasonal products:

thk_<year>_<season>.map.txt.gz (sparse grid)
thk_<year>_<season>.map.complete.txt.gz (complete grid)

3.1.2.2 Data Format

This is an ASCII text file containing 6 columns of data per line. Each line corresponds to a grid location.

The **first** line provides the start and end date of the file:

Column	Field Description	Units
1	Start Day	Day of month
2	Start Month	Month of year
3	Start Year	Year
4	End Day	Day of month
5	End Month	Month of year
6	End Year	Year

Column	Field Description	Units
1	Latitude	Degrees North
2	Longitude	Degrees East
3	Interpolated value of Sea Ice Thickness	meters (can be negative – see note above)
4	Standard Deviation of values used to form thickness at this location	meters
5	Number of values used to form thickness at this location.	Number of measurements
6	Distance of COG of values used from (lat,lon)	km

Second and each subsequent line provides data at each grid location:

3.1.3 NetCDF Format

The files are formatted to be netCDF v3.6 compatible.

3.1.3.1 File Naming

Whole Arctic 5km resolution:

thk_<*days*>.map.<*DD*₁*MM*₁*YY*₁>_<*DD*₂*MM*₂*YY*₂>.nc.gz

1km area sectors:

<days>day_x<X>y<Y>.map. .<DD₁MM₁YY₁>_<DD₂MM₂YY₂>.nc.gz

where *<days>* is either 02, 14 or 28 days, corresponding to the period covered.

 $<DD_1MM_1YY_1>$ is the date of the start of the period covered $<DD_2MM_2YY_2>$ is the date of the end of the period covered

<X> and <Y> are the sector identifiers. There are 36 sectors (as a 6x6 grid) arranged from the bottom left of the Arctic map and spaced every 1110km, such that X=1, Y=1 is the bottom left, and X=6, Y=6 is top right.

3.1.3.2 NetCDF File Format

NetCDF is a self-describing format, which can be shown from its header:

// global attributes: Title = "Arctic Sea Ice Thickness Product from CryoSat";

```
dimensions:
length = <variable> ;
variables:
```



```
short start_day ;
                 units = "day of month(1-31)";
short start_month ;
                 units = "month of year (1-12)";
short start_year ;
                 units = "years YYYY";
short end_day ;
                 units = "day of month (1-31)";
short end month;
                 units = "month of year (1-12)";
short end_year ;
                 units = "years YYYY";
short ndays ;
                 units = "days";
short grid_spacing ;
                 units = "km";
float latitude(length);
                 units = "degrees north";
float longitude(length);
                 units = "degrees east";
float thickness(length) ;
                 units = "meters";
                 long_name = "sea ice thickness" ;
float thk_stdev(length);
                units = "meters";
                 long_name = "standard deviation of thickness at location";
int n_thk(length);
                 units = "number of measurements";
                 long_name = "number of thickness measurements used" ;
float cog_dist(length);
                 units = "km in the projected plane";
         long_name = "distance of centre of gravity from operator centre";
```

Note that the data is in a sparse grid with data points where sea ice thickness measurements are available (5km products). For 1km products all grid points north of 60N latitude (1km products) are included.

3.1.4 GeoTIFF Format

3.1.4.1 File Naming

Whole Arctic 5km resolution:

thk_<*days*>.map.<*DD*₁*MM*₁*YY*₁>_<*DD*₂*MM*₂*YY*₂>.tif

1km area sectors:

<days>day_x<*X*>y<*Y*>.map. .<*DD*₁*MM*₁*YY*₁>_<*DD*₂*MM*₂*YY*₂>.tif

where *<days>* is either 02, 14 or 28 days, corresponding to the period covered.

 $<DD_1MM_1YY_1>$ is the date of the start of the period covered $<DD_2MM_2YY_2>$ is the date of the end of the period covered

<X> and <Y> are the sector identifiers. There are 36 sectors (as a 6x6 grid) arranged from the bottom left of the Arctic map and spaced every 1110km, such that X=1, Y=1 is the bottom left, and X=6, Y=6 is top right.

3.1.4.2 File Format

GeoTIFF files are a TIFF raster image format with added geographic data embedded as tags, allowing precise geo-location of pixels in the image.

For the 5km resolution whole Arctic thickness maps, the TIFF image is stored as an image array of 1335x1335 8-bit pixels. Pixel spacing is 5km.

Pixel 8-bit Value	Sea Ice Thickness
0	0.00m
1	0.02m
2	0.04m
250	5.00m
251-255	not used

Pixel values are scaled in 2cm sea ice thickness increments as follows:

The projection used to map the data is a polar stereographic projection defined by the PROJ.4 (http://trac.osgeo.org/proj) projection string:

<Proj=stere +lat_0=90 +lon_0=0.0 +lat_ts=70.0 +a=6378137 +b=6356752.314 +e= 0.081819191+units=m>

where

Parameter	Description	
lat_0	latitude of origin degrees N	
lon_0*	Longitude of origin (central meridian)	
Lat_ts	Latitude of standard parallel degrees N	
Ellipsoid	WGS84	
a	Semi-major axis radius (m)	
b	Semi-minor axis radius (m)	
е	Eccentricity	
Projection units	meters	
Scaling factor	1	






* note that the projection central meridian is 0 degrees and not -45.0 as is also commonly used for Arctic polar stereo projections such as EPSG:3413.

Image positioning within the projection (x,y) plane is defined by:

Upper left	X (m)	Y (m)
Upper left	-3335000.00	3335000.00
Lower left	-3335000.00	-3335000.00
Upper right	3335000.00	3335000.00
Lower right	3335000.00	-3335000.00
Center	0.0	0.0

GeoTIFF images are provided with a colour palette to match the website's thickness maps.



Note that pixel values (176-250) corresponding to thickness > 3.5m are displayed as pink.